

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: LH-360046G

Date Tested: 12/08/13

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.770	379	6.010	880	9.230	1379
TC2	2.770	380	5.996	880	9.230	1379
TC3	2.777	380	6.007	880	9.238	1381
TC4	2.786	381	6.018	881	9.241	1381
TC5	2.785	382	6.015	882	9.245	1382
TC6	2.781	382	6.017	882	9.250	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: 09/08/13

Precision Digital Voltage Meter SN: 2142011

Calibration Date: 09/08/13

Machine re-calibration due date: 12/08/14

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Gino Rodier Date: 14/08/13

Signature

Montreal Canada office