

Miller ProHeat 35

Unit Serial Number: MB100687G Date Tested: 10/17/2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.788	382	6.018	882	9.246	1382
TC2	2.779	382	6.007	882	9.244	1382
TC3	2.787	382	6.012	882	9.242	1382
TC4	2.794	382	6.020	882	9.247	1381
TC5	2.788	382	6.013	882	9.247	1382
TC6	2.786	382	6.013	882	9.246	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015 Calibration Date: 12/17/12

Precision Digital Voltage Meter SN: 2036021 Calibration Date: 12/17/12

Machine re-calibration due date: 10/17/2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Scott T. Date: 10/17/2013

Signature