

Miller ProHeat 35

Unit Serial Number: MD130337G

Date Tested: 4-10-15

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.787	382	6.013	882	9.233	1382
TC2	2.793	383	6.016	882	9.243	1382
TC3	2.790	383	6.020	883	9.245	1382
TC4	2.800	383	6.024	883	9.250	1383
TC5	2.802	383	6.023	883	9.249	1384
TC6	2.803	382	6.028	884	9.257	1384
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1897018 Calibration Date: 8-4-14

Precision Digital Voltage Meter SN: US36049893 Calibration Date: 8-12-14

Machine re-calibration due date: 4-10-16

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: CHRIS NIETERS

Date: 4-10-15

Signature